



KF4A

Active V-Groove Alignment



Optimized to
Access Network & FTTH installation

ALLINONE+

Benefits and Features

- Remote Maintenance via Internet
- Integrated 7 Function in One Unit (Stripping, Cleaning, Cleaving, Splicing, Protecting, Power Meter and Visual Fault Locator)
- Built-in Power Meter and Fault Locator (PCT/KR2013/001243) -option
- Compatible with Fusion Splice-On Connector(SOC) in accordance with the Industrial Standard



Stripping
(No Cracks on Fiber)



Cleaving



Power Meter and Fault Locator



SOC/Pigtail



On a Telephone pole

Specification

CATEGORY	DESCRIPTION
Fiber alignment	IPAAS Clad to Clad Alignment
Applicable type of fibers	0.25mm, 0.9mm, 2.0mm, 3.0mm Indoor cable
Fiber count	Single fiber
Applicable fiber dimensions	Cladding diameter : 125 μ m, Coating diameter : 150 μ m~3mm
Fiber setting and cleaved length	5mm to 16mm
Splicing modes	Splice mode: 300, Heat mode: 100
Typical splice Loss	SM: 0.02dB, MM: 0.01dB, DS:0.04dB, NZDS: 0.04dB
Return loss	> 60dB
Splicing time	Typical 7sec with SM
Splice loss estimate	Available
Sleeve heating time	Typical 13sec with IS-60 mode, IS-60 sleeve
Applicable protection sleeve	60mm, 40mm and micro sleeves
Storage of splice result	Data : 5,000ea Up to, Image : 5,000ea Up to
Tension test	1.96N to 2.25N
Operating condition	Altitude: 0~5,000m above sea level, Temperature: -10 $^{\circ}$ C~50 $^{\circ}$ C, Humidity: 0~95%, Wind: 15m/s, non-condensing, dust proof, water proof, shock proof
Storage condition	Temperature: -40 $^{\circ}$ C~80 $^{\circ}$ C, Humidity: 0~95%
Dimension	132(W) x 212(L) x 73(H)mm (Without rubber protector)
Weight	1.5kg(Including battery)
Viewing method and display	2 AXIS Two CMOS cameras with 4.3-inch color LCD monitor
Fiber view and magnification	X/Y : 110X , Max :220X
Power supply	Li-ion Battery(DC 14.8V, 3400mAh), 100 ~ 240V AC Charger
No. of splice cycles with battery	Typical 200 cycles
Electrode life	21,000 splices
Terminals	USB

Standard Package

CATEGORY	MODEL	Q'ty
Arc Fusion Splicer	SWIFT KF4A	1
Battery	KF-3400	1
Battery Adapter	FY1701000	1
Instructions for use	-	1
Spare electrode	EI-24	1pair
Transporting Case	HC-11(Hard Case)	1
Optical fiber holder	-	1pair
Cooling Tray	CT-01(40mm)	1
Screw Driver	LD-3300	1
USB Cable	-	1

Option Package

CATEGORY	MODEL
Battery	KF-3400
Cleaver Blade	BI-05
Electrode	EI-24
Transporting Case	ILST-SS03(L)(Soft Case)
Work Belt	WB-01
Sleeve	S09-C, S09, S30-C, S30
Sleeve clamp	SC-01
SOC connector	SC, LC, FC, ST(Refer to FTTx Solution catalogue)
Manual Stripper	CF-02
External Power	DC 12V Available for car cigar jack
Optical fiber holder	HS-250, HS-900, HS-2.5, HS-IN, HF4-SC/FC, HF4-ST, HF4-LC, LS-900(choose one)
Optical Power Module (Optical power meter + VFL)	

ILSINTECH KOREA

#39, Techno 3-ro, Yuseong-gu, Daejeon, Korea (Zip. 305-509)

| Tel +82 42.671.5610 | Fax +82 42.671.5612

USA 4230 LBJ Freeway, Ste.149 Dallas, TX 75244 | (+1) 972 556 0916, (+1) 972 239 5836

CHINA Room 101 Li Ming Building, No111 Gui Qing Road Xuhui District, Shanghai, China | (+86) 21 5836 0950

INDIA ILSintech Trading India Pvt.ltd 621, Devika Tower, Nehru Place New Delhi 110019 | (+91) 11 4055 5954, (+91) 11 4056 7229

RUSSIA Office 401(Kotra) 4F Hotel "Korston" 15 st. Kosygina, Moscow, Russia | (+7) 985 9111987

EUROPE Zirovnicka 2/2389 106 00 Prague 10, Prague, Czech Republic | (+420) 725 001 757

INDONESIA FACTORY Dusun 02 Blok Babakan RT01/Rw03, Desa Sukaraja Wetan, Jatiwangi, Majalengka, Jawa Barat, Indonesia

