

TEST EQUIPMENT

Offered By:



PRO - VIP-35 Video Inspection Probe

VIP-35 / VIP-35-K2 / VIP-35 w/ data storage

The VIP-35 Inspection Probe is designed to provide customers the ability to troubleshoot network performance issues (most commonly caused by dirty connectors) by inspecting the endface of a connector for debris. The VIP-35 kit includes a 400x power probe and a 3.5 inch display for easy viewing of small particles which may exist on the connector. With the included probe tips, the user has the ability to check the quality of both the cable and bulkhead connectors.

PRECISION RATED OPTICS

VIP-35 Kit Includes:

- Hard Carrying Case
- 400X Probe and Monitor
- AC Charger
- FC/SC/ST Bulkhead Adapter
- Adapter
- 2.5mm Universal Adapter

VIP-35 w/Data Storage Kit Includes:

- Hard Carrying Case
- 400X Probe and Monitor
- AC Charger
- FC/SC/ST Bulkhead Adapter
- LC Bulkhead Adapter
- 2.5mm Universal Adapter
- 1.2mm Universal Adapter

VIP-35 Kit 2 Includes:

- Hard Carrying Case
- 400X Probe and Monitor
- AC Charger
- FC/SC/ST Bulkhead Adapter
- LC Bulkhead Adapter
- 2.5mm Universal Adapter
- 1.2mm Universal Adapter

ORDERING INFORMATION

| | |
|-------------|-------------------------------|
| VIP-35 | Video Inspection Probe |
| VIP-35-K2 | Video Inspection Probe Kit 2 |
| VIP-35-DATA | Video Inspection Probe w/data |



VIP-35 w/data

VIP-35 w/data:
3.5" LCD moitor with Image capture and Video record

SPECIFICATIONS

| | VIP-35 | VIP-35 Kit 2 | VIP-35 w/data |
|-----------------------|--------|---|---------------|
| Magnification | | 400X | |
| Screen size | | 3.5 in | |
| Dimensions | | 5.51 x 3.03 x 1.53 in | |
| Weight | | 15.7 oz | |
| Screen type | | TFT Active Matrix | |
| Video output | | PAL / NTSC | |
| Power | | 12V DC Built-in Li-ion Rechargeable Battery | |
| Input Power | | 110-240V AC Adapter | |
| Power supply | | AC or DC Operation | |
| Battery | | 3 Hours | |
| Charging | | 3 Hours | |
| Operating Temperature | | + 4 °F to 122 °F (-10 °C to +50 °C) | |
| Connectors Included | | Universal Patch Cord Tip | |
| Adapters Included | | 2.5mm / 1.25mm / 2.5mm (bulkhead) / LC (bulkhead) | |
| Data Storage | | No | Yes |
| Data Download | | No | Yes |