

501 | Tracker II Cable and Pipe Locator

APPLICATIONS:

With its inductive signal application, the Tracker II can be used on active or dead systems. Now you can trace the path and determine the depth of wires and metallic pipes without having to deactivate the systems. High frequency transmitter provides range up to 4000 feet (1219 m) and depths to 7 feet (2 m). The transmitter offers three methods of connection: direct, inductive coupler, or inductive antenna. Inductive coupler clamps around the wire or pipe for use on active lines or where isolating the line is not an option. Inductive antenna is built into the case housing and allows the transmitter to be placed on the ground over the wire path to radiate a signal down onto the conductor. 32" (813 mm) lightweight receiver provides both audible and visual indications of signal strength for accurate identification. Transmitter output and receiver sensitivity are both fully adjustable for maximum accuracy. Includes transmitter assembly, receiver assembly, inductive coupler (clamp), inductive antenna (built-in), two 8 foot (2.4 m) test leads with heavy-duty alligator clips, and a durable polyethylene case.



FEATURES:

- Three ways of connecting to pipes or cables.
- Traces over distances to 4,000 feet and depths to 7 feet.
- Adjustable Sensitivity.
- Durable Carrying Case.
- Battery-operated (8 - AA and 1 - 9V included).
- 1-year warranty.

BENEFITS:

- Long-Range Wire Locating
- Work on Active or Dead Systems
- Fast, Simple Operation



501 | Tracker II Cable and Pipe Locator

SPECIFICATIONS

Power Source	
Transmitter	Eight "AA" batteries
Receiver	One 9V battery
Battery Life	Transmitter 30 hours, receiver 10 hours nominal
Transmitter Frequency	447.5KHz
Transmitter Power	40Vp-p (140mW) maximum
Voltage Protection	240VAC, 500VDC
Automatic Shut-off	90 min. transmitter & receiver
Construction	
Transmitter/Receiver	Powder coated aluminum
Case	Vacuum formed polyethylene
Dimensions	
Transmitter	4.25 x 3 x 3.25"
Receiver	32 x 2.75 x 4"
Case	33.5 x 8.25 x 3.75"
Weight	6.7 lbs. (complete kit)

ORDERING INFORMATION

Model	Description	UPC
501	Tracker II	08662
HS-1	Headset for 501	08695

RELATED PRODUCTS

Optional headset HS-1 is available for use in high traffic areas or other noisy environments.

